

Mobil Delvac Super 1400 10W-30

Extra High Performance Diesel Engine Oil

Product Description

Mobil Delvac Super 1400 10W-30 is a high performance diesel engine oil specifically engineered to provide excellent lubrication of diesel engines operating in severe applications. This multigrade diesel engine oil is engineered using base oils which provide excellent low temperature fluidity, higher temperature viscosity retention, and volatility control. These base oils are enhanced with an advanced additive system, which provides a high level of protection to all parts of the engine. The optimised viscometrics also provide the opportunity for improved fuel economy. Mobil Delvac Super 1400 10W-30 is recommended for use in most diesel applications including mixed fleets.

Features and Benefits

Lower emission engines place increasing demands on engine lubricants. Tighter engine designs reduce oil consumption, resulting in less fresh oil makeup to replenish depleted additives. Higher piston top rings that bring the oil film closer to higher temperature combustion chambers increase thermal stress on the lubricant. Higher fuel injection pressure and retarded timing improve burn efficiency, but also increase engine temperatures and soot loading of the oil. The technology in Mobil Delvac Super 1400 10W-30 delivers strong performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Good protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Control of high temperature deposits Reduced wear and longer engine life Protection against ring sticking
TBN reserves	Long-term deposit/wear control
Excellent low temperature properties	Ready oil "pumpability" /circulation Start-up wear protection
Stay-in-grade shear stability	Viscosity maintenance and reduced oil consumption under heavy-duty, high temperature operating conditions
High temperature/high shear viscosity maintenance	Reduced engine scuffing and bore polishing protection

Applications

- Diesel powered equipment from leading Japanese, European, and North American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

Mobil Delvac Super 1400 10W-30 meets the following industry and builder specifications:

API CG-4/CF-4/CF

Volvo VDS-2



Mobil Delvac HP-F 10W-30 is recommended for use in applications requiring:

API SF

Mack EO-L

Typical Properties

Mobil Delvac Super 1400 10W-30

SAE Grade	10W-30
-----------	--------

Viscosity, ASTM D 445	
-----------------------	--

cSt @ 40°C	73
------------	----

cSt @ 100°C	11.3
-------------	------

Viscosity Index, ASTM D 2270	146
------------------------------	-----

Sulfated Ash, wt%, ASTM D 874	1.5
-------------------------------	-----

Total Base # , mg KOH/g, ASTM D 2896	11.4
--------------------------------------	------

Pour Point, °C, ASTM D 97	-33
---------------------------	-----

Flash Point, °C, ASTM D 92	206
----------------------------	-----

Density @ 15°C kg/l, ASTM D 4052	0.88
----------------------------------	------

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, Mobil and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.