

# Mobilfluid 426

## Extra High Performance Multipurpose Tractor Fluid

### Product Description

Mobilfluid 426 is an extra high performance multipurpose tractor lubricant engineered to meet or exceed transmission and hydraulic fluid requirements. The advanced technology in Mobilfluid 426 is designed to optimise the performance of agricultural and commercial tractors operating in a wide range of environments and conditions. This next generation product combines select base oils and an advanced additive package to deliver the varied lubricant performance properties required by the drive trains of agricultural and construction equipment proven in severe duty applications. It is particularly well suited for reducing wet brake and Power Take-Off (PTO) chatter.

### Features and Benefits

Next generation technology has vastly improved the performance capabilities of heavy-duty equipment in terms of load, speed, control, and reliability through innovative powertrain designs. These designs have changed and increased the requirements of powertrain fluids to deliver higher levels of performance and productivity while reducing operating costs. Friction control, wear protection, thermal stability, shear stability, rust and corrosion protection, and pumpability are features that must be optimally balanced to provide extended clutch life, maximum drawbar loading, and maintain operations on uneven terrain over a wide range of ambient temperatures. Mobilfluid 426 delivers exceptional performance in today's power train transmissions, drive axles, clutches, PTOs and hydraulic systems. The key benefits include:

Features	Advantages and Potential Benefits
Enhanced frictional properties	Optimised clutch and PTO performance Improved wet brake and PTO chatter control
Compatible with clutch materials and elastomers	Longer clutch life and reduced leakage
High viscosity index and improved shear stability	Consistent operating response
Excellent protection against rust, corrosion, and yellow metal etching	Protects equipment in wet or humid environments and prevents premature wear
Excellent low temperature properties	Responsive operation and effective lubrication in cold weather applications
Strong anti-wear and extreme pressure properties	Reduces wear, extends equipment life, and reduces maintenance costs
Good thermal and oxidation stability	Reduces deposits, extends seal life, and increases service life of equipment and lubricant
Multipurpose capability	Simplifies inventory and reduces misapplication problems
Good filterability	Keeps systems clean and operating smoothly

### Applications

- Heavy-duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTOs and hydrostatic drives
- Recommended in off-highway industries including: agriculture, construction, and quarrying
- Recommended for top-up and refill of systems



- Suitable for commercial transmission applications requiring Type A (Suffix A), Dexron and Type F fluids. Do not use in passenger car automatic transmissions
- May be used in applications requiring API GL-4 or SAE 80W grade lubricants in all gear applications except hypoid gear designs
- Recommended for replacement for engine oils (up to 10W-30 grade) for hydraulic and transmission systems

## Specifications and Approvals

---

### Mobilfluid 426 meets the following industry and builder specifications:

API GL-4

AGCO Powerfluid 821 XL

Ford New Holland FNHA-2-C-201.00

Case New Holland CNH 134-D

Kubota UDT

John Deere J20C

Vickers 35VQ25

Volvo WB 101/BM

Massey Ferguson MF 1143

---

### Mobilfluid 426 has the following builder approval:

ZF-TE-ML 03E

---

### Mobilfluid 426 is also recommended for use in applications requiring:

Allison C-4 (Agriculture Only)

Caterpillar TO-2

Denison HF-0, HF-1, HF-2 (Pumps only)

J. I. Case MS 1204-07/09

Massey Ferguson MF 1135, 1141

UTTO

Ford New Holland ESN-M2C-134D

---

## Typical Properties

### Mobilfluid 426

Viscosity, ASTM D 445

cSt @ 40°C	59
------------	----

cSt @ 100°C	9.7
-------------	-----

Brookfield Viscosity, cP (@ -20°C)	3800
------------------------------------	------

Viscosity Index, ASTM D 2270	149
------------------------------	-----

Pour Point, °C, ASTM D 97	-39
---------------------------	-----

Flash Point, °C, ASTM D 92	228
----------------------------	-----

Density @ 15°C kg/l, ASTM D 4052	0.889
----------------------------------	-------

---



## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Toxicity class: free BAG T No.: 621000

*The Mobil logotype, the Pegasus design, and Mobilfluid 426 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.*