

Mobil Super 3000 XE 5W-30

Description

Mobil Super 3000 XE 5W-30 is a synthetic high-performance low ash engine oil designed to help prolong the life and maintain the efficiency of the Exhaust Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

Features and Benefits

- Helps to maintain the efficiency of the Exhaust Emission Reduction systems in both diesel and gasoline vehicles.
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in both gasoline and diesel engine passenger car and light commercial vehicles.

Application

Mobil Super 3000 XE 5W-30 has been developed to meet the latest specifications for engine oils required by major car manufacturers and is compatible with most latest Diesel Particulate Filters and all gasoline catalytic converters.

Mobil Super 3000 XE 5W-30 offers excellent performance at both very low and very high operating temperatures and long term engine protection from wear and sludge and deposit build-up.

Mobil Super 3000 XE 5W-30 is specially recommended for use in Mercedes-Benz vehicles (requiring a MB 229.31 or 229.51 approved product), in BMW vehicles (requiring Longlife Oil 04) and in Volkswagen vehicles (requiring a VW 502 00 / 505 00 approved product).

Mobil Super 3000 XE 5W-30 is also intended for use in Volkswagen TDI pump-jerk engines (oil change intervals : 15000 km / 1 year) requiring a VW 505 01 approval and in Ford Galaxy 1.9L Turbo Diesel requiring a VW 505 01 or a Ford WSS-M2C917-A approval.

Mobil Super 3000 XE is also suitable for applications requiring the new General Motors / Opel / Vauxhall low ash specification.

Specifications

Mobil Super 3000 XE 5W-30 meets or exceeds the following industry specifications:

ACEA	C3, A3/B3, A3/B4
API	SM/CF
Ford	WSS-M2C917-A



Mobil Super 3000 XE 5W-30 has the following builder approvals :

BMW	Longlife 04
MB-Approval	229.31/229.51
Volkswagen (Gasoline / Diesel)	502 00 / 505 00 / 505 01

Typical Properties

Mobil Super 3000 XE 5W-30

Viscosity, ASTM D 445	
cSt @ 40° C	68
cSt @ 100° C	11.9
Sulfated Ash, wt%, ASTM D 874	0.8
Phosphorous	0.08
Flash Point, °C, ASTM D 92	230
Density @15° C kg/l, ASTM D 4052	0.85
Pour Point, °C, ASTM D 97	-36

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobilcut are trademarks of ExxonMobil Corporation, or one of its subsidiaries.