

Mobil Super FE Special 5W-30

Premium Quality Multigrade Semi-Synthetic Motor Oil

Product Description

Mobil Super FE Special 5W-30 is a premium quality semi synthetic engine oil developed to the highest standards of lubricant quality, reliability and dependable protection.

Features and Benefits

Mobil Super FE Special 5W-30 is formulated with a proprietary mixture of premium and super premium quality synthetic baseoils with additive technology that provides outstanding engine protection under a variety of operating conditions. This oil is approved by Ford and meets requirements for service fill use in their most recent models. Key features and benefits include:

- Excellent oxidation stability to reduce engine deposits and sludge build-up to keep engines running reliably
- Excellent high and low temperature properties to provide dependable protection across a wide range of driving conditions
- Enhanced low temperature capabilities for outstanding cold weather starting

Applications

Mobil Super FE Special 5W-30 can be used in a variety of gasoline and diesel automobiles, light trucks and vans, and for anyone seeking a dependable super premium quality product.

Mobil Super FE Special 5W-30 is intended primarily to meet the requirements of Ford WSS-M2C913-A and M2C913-B for service use but is also suitable for use in other vehicles where the viscosity and quality claims are appropriate.

Specifications and Approvals

Mobil Super FE Special 5W-30 meets or exceeds the following industry specifications:

API SL

ACEA A1/B1

Ford WSS-M2C913-A

Ford WSS-M2C913-B

ILSAC GF-3

Typical Properties

Mobil Super FE Special 5W-30

Viscosity, ASTM D 445

cSt @ 40° C

58.6



Mobil Super FE Special 5W-30

cSt @ 100° C	10.6
Sulfated Ash, wt%, ASTM D 874	1.05
Phosphorous	0.1
Flash Point, °C, ASTM D 92	225
Density @ 15° C kg/l, ASTM D 4052	0.85
Pour Point, °C, ASTM D 97	-51

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.